OrthoProMed.com

Medical Supplies, Instruments, Implants

Orthopromed Medical Supplies INC.
Phone : +852 8191 3424
Email : info@orthopromed.com
Address : Building D, 15th Guotai North Road, Zhangjiagang City, Jiangsu Province, CHINA

MODEL OTS-1 BONE OSCILLATING SAW

Main features:
◆ Main unit can be sterilized by high temperature and high pressure up to 135°C
◆ Powerful, portable, variable speed control without step, precise and stable.
◆ Motor is made in Switzerland.
◆ For all kinds of joint operation.

Technical data :
◆ Motor : Working voltage： 14.4V
Output power: ≥80W
◆ Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
◆ Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
◆ Saw frequency: 0—15000 times/minute ±20%
◆ Oscillating amplitude: 3-8°
◆ Noise Level: ≤70 DB

MODEL OTS-2 BONE DRILL

Main features:
◆ Main unit can be sterilized by high temperature and high pressure up to 135°C
◆ Powerful, portable, variable speed control without step, precise and stable.
◆ Running direction : Forward and Opposite
◆ Motor is made in Switzerland.
◆ For Trauma operation.

Technical data :
◆ Motor : Working voltage： 14.4V
Output power: ≥80W
◆ Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
◆ Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
◆ Speed: 0—1200 RPM (Variable speed control) ±20%
◆ Noise Level: ≤70 DB

MODEL OTS-3 CANNULATED DRILL

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- With a cannula diameter of 4.0mm, holds K-wires or hold Flexible reamer in intramedullary interlocking nail operation
- Running direction : Forward and Opposite
- Motor is made in Switzerland.
- For Trauma operation.

Technical data :
- Motor : Working voltage： 14.4V

Output power: ≥80W
- Charger: Input voltage： AC 110V-240V, 50Hz
  Output voltage： 14.4V
  Charging time: half Hour
- Battery: Voltage: 14.4
  Charging time: half Hour
  Capacity: ≥ 1 hour
  Needn't to be sterilized
- Speed: 0—600 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTS-4 DUAL FUNCTION CANNULATED DRILL

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Can be attached with Flexible reamer on handpice directly, with a attachment Jacob chuck to accept any type of Flexible reamer and cannula diameter of 4.0mm to holds K-wires
- Running direction : Forward and Opposite
- Motor is made in Switzerland.
- For Trauma operation.

Technical data :
- Motor : Working voltage： 14.4V

Output power: ≥80W
- Charger: Input voltage： AC 110V-240V, 50Hz
  Output voltage： 14.4V
  Charging time: half Hour
- Battery: Voltage: 14.4
  Charging time: half Hour
  Capacity: ≥ 1 hour
  Needn't to be sterilized
- Speed: 0—600 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTS-5 ACETABULUM BURNISHING REAMER

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Low speed, large torque, Can be attached with Acetabulum burnishing reamers on handpice directly, and with a attachment Jacob chuck to accept any type of acetabulum burnishing reamers
- Running direction : Forward and Opposite
- Motor is made in Switzerland.
- For Joint operation.

Technical data :
- Motor : Working voltage： 14.4V
Output power: ≥80W
- Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Speed: 0—600 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTS-6 STERNUM SAW

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Motor is made in Switzerland.
- For Thoracic operation

Technical data :
- Motor : Working voltage： 14.4V
Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Saw frequency: 0—12000 times/minute ±20%
- Noise Level: ≤70 DB

MODEL OTS-7 BONE RECIPROCATING SAW

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Motor is made in Switzerland.
- For Joint surgery

Technical data :
- Motor : Working voltage： 14.4V
Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Saw frequency: 0—10000 times/minute ±20%
- Noise Level: ≤70 DB

MODEL OTS-8 CRANIAL DRILL

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Self-stopped after drill through to assure the safety of the operation
- Motor is made in Switzerland.
- For Neurosurgery

Technical data :
- Motor : Working voltage： 14.4V
Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Speed: 0—500 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTS-9 CRANIAL BUR

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Motor is made in Switzerland.
- For Neurosurgery

Technical data :
- Motor : Working voltage： 14.4V
Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz
Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4
Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Speed: 0—50000 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTSS01 BONE OSCILLATING SAW

Standard configurations:
- Handpiece + 2 batteries + electrical charger + sterilizing channels+ 2 saw blades
- Package : Aluminium box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- For all kinds of joint operation

Technical data :
- Motor : Working voltage： 14.4V Output power: ≥100W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V
Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
- Saw frequency: 0—15000 times/minute ±20%
- Oscillating amplitude: 3-8°
- Noise Level: ≤70 DB

MODEL OTSS02 BONE DRILL

Standard configurations:
◆ Handpiece + 2 batteries + electrical charger+ sterilizing channels + 2 drill bits
◆ Package : Aluminum box
Main features:
◆ Main unit can be sterilized by high temperature and high pressure up to 135°C
◆ Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
◆ Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
◆ Lithium battery, durable, stable and light
◆ Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
◆ Running direction : Forward and Opposite
◆ For all kinds of joint operation
Technical data :
◆ Motor : Working voltage： 14.4V Output power: ≥100W
◆ Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V
Charging time: half Hour
◆ Battery: Voltage: 14.4V Charging time: half Hour
Capacity: ≥ 1 hour
Needn't to be sterilized
◆ Speed: 0—1200 RPM (Variable speed control) ±20%
◆ Noise Level: ≤70 DB

MODEL OTSS03 CANNULATED DRILL (WIRE AND PIN DRILL)

Standard configurations:
◆ Handpiece + 2 batteries + electrical charger+ sterilizing channels
◆ Package : Aluminum box
Main features:
◆ Main unit can be sterilized by high temperature and high pressure up to 135°C
◆ Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
◆ Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
◆ Lithium battery, durable, stable and light
◆ Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
◆With a cannula diameter of 4.0mm, holds K-wires or hold Flexible reamer in intramedullary interlocking nail operation
◆ Running direction : Forward and Opposite
◆ For all kinds of joint operation
Technical data :
◆ Motor : Working voltage： 14.4V Output power: ≥100W
◆ Charger: Input voltage： AC 110V-240V, 50Hz
◆ Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
◆ Speed: 0—900 RPM (Variable speed control) ±20%
◆ Noise Level: ≤70 DB

MODEL OTSS04 DUAL FUNCTION CANNULATED DRILL (WIRE AND PIN DRILL)

Standard configurations:
- Handpiece + 2 batteries + electrical charger+ sterilizing channels
- Package : Aluminum box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- Can be attached with Flexible reamer on handpice directly, with a attachment Jacob chuck to accept any type of Flexible reamer and cannula diameter of 4.0mm to holds K-wires
- Running direction : Forward and Opposite
- For all kinds of joint operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥100W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Speed: 0—900 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTSS05 ACETABULUM BURNISHING REAMER

Standard configurations:
- Handpiece + 2 batteries + electrical charger+ sterilizing channels
- Package : Aluminum box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- Low speed, large torque, Can be attached with Acetabulum burnishing reamers on handpice directly, and with a attachment Jacob chuck to accept any type of acetabulum burnishing reamers
- Running direction : Forward and Opposite
- For joint operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥100W
- Charger: Input voltage：AC 110V-240V, 50Hz, Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Speed: 0—700 RPM (Variable speed control) ±20%
- Noise Level: ≤70 D

MODEL OTSS06 STERNUM SAW (RECIPROCATING SAW)

Standard configurations:
- Handpiece + 2 batteries + electrical charger+ sterilizing channels+ 2 saw blades
- Package : Aluminum box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- For thoracic operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥100W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Saw frequency: 0—12000 times/minute ±20%
- Noise Level: ≤70 DB

MODEL OTSS07 CRANIAL DRILL

Standard configurations:
- Handpiece + 2 batteries + electrical charger+ sterilizing channels+ 2 saw blades
- Package : Aluminum box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- For cranial operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Speed: 0—700 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OTSS08 CRANIAL BUR

Standard configurations:
- Handpiece + 2 batteries + electrical charger+ sterilizing channels+ 2 saw blades
- Package : Aluminum box

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Swiss Motor , Powerful, portable, variable speed control without step, precise and stable.
- Integrated Stainless Steel handpiece shell, light, clean safety and beautiful
- Lithium battery, durable, stable and light
- Dual batteries type Charger, can charge 2 batteries at same time, quickly and safely
- For cranial operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Speed: 0—50000 RPM (Variable speed control) ±20%
- Noise Level: ≤70 DB

MODEL OT1001 BONE OSCILLATING SAW

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- For all kinds of joint operation.

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1002 BONE DRILL

from $550

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Running direction : Forward and Opposite
- For all kinds of joint operation.

Technical data :
- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1003 CANNULATED DRILL

from $550

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Running direction : Forward and Opposite
- For all kinds of joint operation.

Technical data :
- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1004 DUAL FUNCTION CANNULATED DRILL

Main features:

- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Can be attached with Flexible reamer on handpice directly, with a attachment Jacob chuck to accept any type of Flexible reamer and cannula diameter of 4.0mm to holds K-wires
- Running direction : Forward and Opposite
- For all kinds of joint operation.

Technical data :

- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1005 ACETABULUM BURNISHING REAMER

Main features:

- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Low speed, large torque, Can be attached with Acetabulum burnishing reamers on handpice directly, and with a attachment Jacob chuck to accept any type of acetabulum burnishing reamers
- Running direction : Forward and Opposite
- For joint operation.

Technical data :

- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1006 STERNUM SAW

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- For thoracic operation

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1007 BONE RECIPROCATING SAW

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1008 CRANIAL DRILL

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- Self-stopped after drill through to assure the safety of the operation
- For cranial operation

Technical data :
- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OT1009 CRANIAL BUR

Main features:
- Main unit can be sterilized by high temperature and high pressure up to 135°C
- Powerful, portable, variable speed control without step, precise and stable.
- For cranial operation

Technical data :
- Motor : Working voltage： 14.4V Output power: ≥70W
- Charger: Input voltage： AC 110V-240V, 50Hz Output voltage： 14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MODEL OTM MULTIFUNCTION TYPE ORTHOPAEDIC SAW DRILL

Main Features:
1. Multifunction designed, convenient and economical.
2. Can be used in all kinds of Joint and Trauma operations: Oscillating saw function, Bone drill function(or AO drill), Cannulated drill function, K wire and pin drill function, Acetabulum burnishing drill function, Flexible reamer function.
3. Autoclavable, can be sterilized by high temperature and high pressure up to 135°C.
4. Brushless motor made in Switzerland, stepless speed changing, powerful, stable and low noise.
5. Big energy Ni-MH battery, quickly chargered and anti-explosion design, powerful and safety.
6. Handpiece is hard and light, comfortable to be holded for the surgeons.
7. CE and ISO approved

Technical data :
- Motor : Working voltage：14.4V Output power: ≥70W
- Charger: Input voltage：AC 110V-240V, 50Hz Output voltage：14.4V, Charging time: half Hour
- Battery: Voltage: 14.4V Charging time: half Hour, Capacity: ≥ 1 hour, Needn't to be sterilized
- Noise Level: ≤70 DB

MULTIFUNCTION TYPE COMBINATIONS

MULTIFUNCTION TYPE(COMBINATION I)

Specifications:
1, Configuration: Handpiece + Bone saw + Bone drill + 2 Batteries + Charger + 4 Saw blades + other accessories
2, For Joint and Trauma surgery

MULTIFUNCTION TYPE(COMBINATION II)

Specifications:
1, Configuration: Handpiece + Bone saw + Bone drill + Cannulated drill+ 2 Batteries + Charger + 4 Saw blades + other accessories
2, For Joint and Trauma surgery

MULTIFUNCTION TYPE(COMBINATION III)

Specifications:
1, Configuration: Handpiece + Bone saw + Cannulated drill + Acetabulum burnishing drill + 2 Batteries + Charger + 4 Saw blades + other accessories
2, For Joint and Trauma surgery

MULTIFUNCTION TYPE(COMBINATION IV)

Specifications:
1, Configuration: Handpiece + Bone saw+ Bone drill + Cannulated drill + Acetabulum burnishing drill + 2 Batteries + Charger + 4 Saw blades + other accessories
2, For Joint and Trauma surgery

MULTIFUNCTION TYPE(COMBINATION V)

Specifications:
1, Configuration: Handpiece + Bone drill + Cannulated drill + 2 Batteries + Charger + other accessories
2, For Trauma surgery

MULTIFUNCTION TYPE(COMBINATION VI)

Specifications:
1, Configuration: Handpiece + Cranial drill+ Crania bur + 2 Batteries + Charger +2 pcs bur bits + other accessories
2, For Neurosurgery

MODEL OTMI MICRO TYPE SUGICAL SAW DRILL

from $2650

Main Features:
1. A/C powered . Powerful, Stable, Reliable, high speed and low noise.
2. Use: Neurosurgery, Spine surgical, Plastic surgery, E.N.T surgery, Facial surgery, Orthopaedic surgery and so on.
3. Can be sterilized by high temperature and high pressure up to 135°C

MICRO TYPE(COMBINATION I)

Specifications:
Power control unit + Pedal switch + Micro Motor + Micro Curved Drill(OTMI-2) + 4 pcs of burs

$2650

MICRO TYPE(COMBINATION II)

Specifications:
Power control unit + Pedal switch + Micro Motor + Micro Straight Drill(OTMI-1) + Micro Curved Drill(OTMI-2) + 4 pcs of burs

$3350

MICRO TYPE(COMBINATION III)

Specifications:
Power control unit + Pedal switch + Micro Motor+ Micro Straight Drill(OTMI-1) + Micro Curved Drill(OTMI-2) + Micro Oscillating saw(OTMI-3) + 4 pcs of burs + 2 pcs of saw blades

$4390

MICRO TYPE(COMBINATION IV)

Specifications:
Power control unit + Pedal switch + Micro Motor + Micro Straight Drill(OTMI-1) + Micro Curved Drill(OTMI-2) + Micro Oscillating saw(OTMI-3) + Micro Reciprocating Saw (OTMI-4) + 4 pcs of burs+ 4 pcs of saw blades

$5450